

COAXIAL/R-S02Y(St)CY 1x1.0 P
Code - 10281



Description

Bare copper conductor. Physical foam polyethylene insulation. Aluminium-polyester-aluminium foil shield. Tinned copper braid shield. PVC outer sheath.

PHYSICAL CHARACTERISTICS

Conductor

Material	Bare copper
Section (mm ²)	0,78
AWG	24
Composition	1 x 1,0

Insulation

Material	Physical foam polyethylene
Diameter (mm)	4,60
Colour	natural

Shield

1st Shield	
Material	Aluminium-polyester-aluminium foil
Coverage	100 %
2nd Shield	
Material	Tinned copper braid
Coverage	90 %

Outer sheath

Material	PVC
Diameter (mm)	7
Colour	Black



**COAXIAL/R-S02Y(St)CY 1x1.0 P
Code - 10281**

Printing

Inscription	Conducfil
-------------	-----------

Supply

Packing	To be defined
---------	---------------

MECHANICAL CHARACTERISTICS

Appox. Weight	47,5 Kg/km
Operating temperature range	-20 / +80
Minimum bending radius	140 mm

ELECTRICAL CHARACTERISTICS

Conductor DC resistance at 20° C	22 Ohms/km
Shield DC resistance at 20° C	9,4 Ohms/Km
Nominal capacitance	54 pF/m
Nominal impedance	75 ohms
Velocity of propagation	82 %

Attenuation	Frequency (MHz)	dB/100 m
	1	0,8
	5	1,7
	10	2,4
	20	3,2
	30	3,7
	50	4,5
	100	6,1

Return loss	Frequency (MHz)	dB
	0-800	20
	800-1000	23

Insulation resistance	>5000 Mohms * Km
-----------------------	------------------

Voltage test	1500 v
--------------	--------



COAXIAL/R-S02Y(St)CY 1x1.0 P
Code - 10281

SAFETY

FLAME TEST

		Compliance
Test for vertical flame spread	IEC-60332-1	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-2	<input type="checkbox"/>
Test for vertical flame spread	IEC-60332-3	<input type="checkbox"/>
It does not emite toxic fumes or halogens	IEC-754-1	<input type="checkbox"/>
It does not emite corrosive fumes or halogens	IEC-754-2	<input type="checkbox"/>
Low emision of dense fumes	IEC-1034-1	<input type="checkbox"/>

ENVIRONMENT

		Compliance
Content of hazardous sustances	Directive 2002/95/CE	<input checked="" type="checkbox"/>

APPLICABLE SPECIFICATIONS

		Compliance
Conductor material	UNE-EN 60228	<input checked="" type="checkbox"/>
Insulation material	UNE-EN 50290	<input checked="" type="checkbox"/>